
NATE



LIFTING COLUMN


JRF2-D5

Product Data Sheet

www.natekj.com

NATE DRIVE

NT33- JRF2-D5



The JRF2-D5 is a two-section, non-perforated lifting device with an outer rectangular tube measuring 80 x 50 mm.
The support column is suitable for various desktop application needs; it is inverted .
The mounting hole positions of JRF2-D5 are the same as those of other rectangular tube lifting columns such as JRF3-D5 , therefore ...
Given the same desktop and feet, choose the appropriate option based on your actual needs.
The lift column. For solutions involving opposite tables, the lift column can be equipped with pads and connecting links.
Used in conjunction with the connecting rod.

The JRF2 -D5 rising bollard is available in three standard color schemes (black, gray, and white), but is also available in other colors.
Other colors can be selected as needed. The column has an obstacle detection and reversing function to maximize its stability.
This reduces the risk of the standing table encountering obstacles.

The JRF2 -D5 can be paired with a variety of NATE custom hand controllers, allowing customers to choose according to their specific needs.
Choose one with features such as USB charging, location memory, and child lock.

characteristic :

- Enhanced lifting column with optimized motor housing design, offering higher strength and stability.
- Maximum load : 800 N per lifting column
- Maximum speed: 30 mm /s (unloaded)
- Installation dimensions : 66.5 mm
- Travel: 500 mm
- Weight: Approximately 6 kg per lifting column
- Operating sound : < 50 dB
- Dimensions of the lifting bollard : 80 x 50 mm (Exterior) 75 x 45 mm (Interior)
- Motor housing dimensions: 183 x 147 x 49 mm
- Colors: Available colors: Black (RAL Eggshell Gloss 9005) , Silver Gray (Silver Gray EM Semi-gloss 2921), White (Semi-gloss 9016 Off-white)
- Quiet, calm

Options :

• Optional matching placemats

use:

• Two lifting columns driven synchronously ; one controller, one manual controller.

• Duty cycle: 10% ≈ 2 minutes of continuous full-load use , then pause.

18 minutes

• Ambient temperature: 10 to 40 ° C


• Storage and transport temperature: -10 to +70 ° C

• For system compliance information, please refer to the "Conformity Declaration " in the User Manual.

With a fully retracted length of 665 mm and a travel length of 500 mm , the standard system offers a desktop height adjustment interval of 700 mm to 1200 mm , allowing the desk to be used for both seated and standing work.

JRF2-D5

Order instance :




F denotes no holes, A denotes standard orientation, R denotes inverted orientation.

Note: For double tables, use the two vertical columns at positions A1 and A2 with spacers. For single tables, add a cross brace using the two vertical columns at position A3 with spacers.


Dimensions

All measurements do not include the thickness of the powder coating.




Version	Combination code	B (Installation Dimensions) [mm]	S (Itinerary) [mm]	O (outer tube length) [mm]
EU	JRF2-D5 xxxx 500 / 665	665	500	600


F2-D5 Installation Dimensions, Stroke, and Outer Tube Length (mm)



Motor housing outline



Fixed dimensions for the base of the rising bollard



JRF2-D5 dimensions(mm)

For installation instructions and usage guidelines, please refer to the relevant user manual.